BLUESLIM

ADBLUE CONTAINER

Store AdBlue on your station

Container's technical specifications

- Galvanized steel structure with 32 mm aluminium high gloss white double-walled panels
- □ Built-in 80 L/min submersible pump with 2m length flexible discharge hose
- □ High density polypropylene tank
- □ Filling plug with TODO coupling installed at the front or rea
- □ High and low level sensor with alarm
- Air vent
- Temperature regulated heater
- Upper and lower natural ventilation
- Access hatch on the roof for gauge insertion
- Transportable by fork lift truck when empty

Options

- □ Chassis for TATSUNO GILBARCO TOKHEIM dispensers
- □ SNE electronic gauge
- Pump for return into tank (after metrological controls)

Capacity	Length	Width	Height	Weight (empty)
2000 L	2.50 m	1.03 m	2.37 m	550 Kg
3000 L	2.50 m	1.03 m	2.37 m	650 Kg

Front view

STATE OF THE PARTY NAMED IN	THE RESIDENCE OF THE PARTY OF T
Reference	Description
BLUESLIM2	2000 L ADBLUE CONTAINER
BLUESLIM3	3000 L ADBLUE CONTAINER
BLUECHx	CHASSIS FOR DISPENSER
BLUEREL	LIFT PUMP

Lateral view

