

ECODIS-200

FUEL DISPENSER

Dispense all fuels at very high flow-rate.

Dispenser's technical specifications

- ❑ Dispense all fuels, flow-rate up to 200 liters/minute
- ❑ Two 380 volts three-phase ex-proof motors : II 2G Ex d IIB
- ❑ Two self-priming vane pumps
- ❑ Two air separators
- ❑ Two 4 pistons flow meters of approx. 0,2 % accuracy
- ❑ Two dual-channel sensors Ex dII BT4
- ❑ High-gloss epoxy painted steel body
- ❑ Door closing system by key locks
- ❑ Drip tray at the bottom
- ❑ ZVA 32 automatic nozzle with swivel
- ❑ 4 meters length EN1360 Ø 32 hose
- ❑ Hydraulic connection by two 1½ " triangular flanges + tee-fitting
- ❑ Dimensions : L. 960 / W. 400 / H. 1460 mm
- ❑ Weight (standard version) : approx. 160 kg

Options available

- ❑ SSB break-away swivel
- ❑ Emergency stop button
- ❑ Additional Ø 32 hose length
- ❑ Custom painting
- ❑ Integration of an automaton or calculator
- ❑ Adapters for connection to above-ground tank
- ❑ Single phase 240 VAC motors
- ❑ Thermal protection of motors
- ❑ Water separator filter
- ❑ Additional output for satellite connection
- ❑ Emergency crank for manual delivery
- ❑ Stainless steel body



Hydraulics

Reference	Description
ECODIS-200	200 L/min galvanized steel dispenser
ECODIS-200-I	200 L/min stainless steel (316l) dispenser
VCD007	Key switch locking system
AU007	Emergency stop button
CA701	LCD electronic calculator

ALX
TECHNOLOGIES