

# GA811

## ACCESS CONTROL

### ACCESS CENTER – GA811

Manages access authorizations for 1900 agents on max. 32 access points. It is programmed from the ALX LV8 or LVNET fuel management software.

Each agent is associated with work schedules and licensed locations.

Each access is defined by free access schedules and controlled zones.

At the beginning and at the end of free access schedules, it is possible to open (or close) automatically.

Forced opening / closure at any time from the software.

#### DESCRIPTION :

- Metal casing 50 x 210 x 140 mm
- Power supply 240 VAC (the GA811 can power up 5 access controls).



### Keypad access control – ACD002

Keypad that can operate in external environment and also allows bonding a dry contact for the opening of a portal or an access barrier.

#### PERFORMANCES :

- Output of a message in real-time on the automaton's printer
- Max. connection distance : 800m
- Each access point is identified by a number
- Wired directly on the automaton or on the GA811.

#### DESCRIPTION :

- 12VDC power supply (not provided)
- Metal case for wall mounting
- Electronic board with buzzer



Reference	Description
GA811	Access center
ACD002	Keypad access control
AL12	12 V 1A power supply

## Access control by contactless keys – ASC002

SC257 contactless key reader that can operate in external environment and also allows bonding a dry contact for the opening of a portal or an access barrier.

### PERFORMANCES :

- Use with ALX contactless keys ref. SC257 or SCP127
- Max. connection distance : 800m
- Each access point is identified by a number
- Wired directly on the automaton or on the GA811.

### DESCRIPTION :

- 12VDC power supply (not provided)
- Metal case for wall mounting



## Access control by magnetic cards – ABMW002

Magnetic card reader that can operate in external environment and also allows bonding a dry contact for the opening of a portal or an access barrier.

### PERFORMANCES :

- Use with standard tankers magnetic cards or with ALX magnetic cards
- Max. connection distance : 800m
- Each access point is identified by a number
- Wired directly on the automaton or on the GA811.

### DESCRIPTION :

- Waterproof card reader
- 12VDC power supply (not provided)
- Metal case for wall mounting



## Access control by radio remote control – ARD002

Radio receiver that can operate in external environment and also allows bonding a dry contact for the opening of a portal or an access barrier.

### PERFORMANCES :

- Use with TC002 remote keys reach 15 – 20 meters
- Max. connection distance : 800m
- Each access point is identified by a number
- Wired directly on the automaton or on the GA811.

### DESCRIPTION :

- 12VDC power supply (not provided)
- Metal case for wall mounting



Reference	Description
ASC002	Access control by contactless keys
ABMW002	Access control by magnetic cards
ARD002	Access control by radio remote control
TC002	Remote control for ARD002
AL12	12 V 1A power supply